



Omnidirectional Reception



Recreational Vehicle Antenna

CA-1500, CA-2500



UHF/VHF
HDTV



Omnidirectional



UV
Resistant



Powered
Amplifier



Low
Profile

External HDTV RV Antenna

Specifications	CA-1500	CA-2500
Input Power	9VDC - 16VDC	9VDC - 16VDC
Operating Temperature	-25°F - 145°F	-25°F - 145°F
Impedance	75 Ohm	75 Ohm
Frequency Video Range	87MHz - 698MHz	54 MHz - 698 MHz
Frequency Audio FM	87MHz - 108MHz	87 MHz - 108 MHz
Frequency Audio AM	None	500 kHz - 1800 kHz
Directivity	Omni (no pointing req.)	Omni (no pointing req.)
Mounting Base	High Impact Plastic	High Impact Plastic
Dimension Length	35"	48"
Dimension Height	7"	7"
Weight	3.3 lbs.	3.4 lbs.
Color	Black or white body	Black or white body
Warranty	One year parts and labor	One year parts and labor
Signal Distribution	CA-1500	CA-2500
Output Terminal	2 RF Jacks	4 RF Jacks
Radio Output	FM	AM/FM
Impedance	75 Ohm	75 Ohm
Gain	20 dB	20 dB
Directivity	Omni (no pointing req.)	Omni (no pointing req.)

